

SECTION 1 - MANUFACTURER INFORMATION

MANUFACTURER/ DISTRIBUTOR: COMMODORE SALES, INC.
11002 TRADE ROAD
RICHMOND, VA 23236

PREPARER/CONTACT: JOHN CROWE
EMERGENCY PHONE: (800)535-5053 (INFOTRACK)
INFORMATION PHONE: (804)794-1992

TRADE NAME / SYNONYMS. . . : PAINT SEALANT RENEWER
CHEMICAL NAME / SYNONYMS: SILICON, WAX, & CLEANER.
CHEMICAL FAMILY. : NOT APPLICABLE
FORMULA. : Proprietary
PRODUCT CODE. : 25-079

SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29B1910.1200 (i)-(13)
CHEMICAL / COMMON NAME CAS# PERCENTAGE PEL-OSHA TLV ACGIH
*Aliphatic Hydrocarbons 8052-41-3 >1 100ppm 100ppm

THIS PRODUCT DOES NOT CONTAIN REGULATED PRODUCTS OR PRODUCTS THAT ARE KNOWN TO CAUSE CANCER:
(NTP, IARC, OSHA):

All items marked with asterisk()are toxic chemicals subject to the reporting requirements of section 313 of Title III of the superfund Amendments and Reauthorization Act (SARA) of 1986 and CFR 40 Part 372. You must notify each person to whom this mixture or trade name product is sold or used. This statement is part of this Material Safety Data Sheet (MSDS).

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

Acute:

- a)Eyes - Can cause irritation, redness, tearing, blurred vision & swelling.
- b)Skin - Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
- c)Inhalation - Vapors can cause nasal & respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and asphyxiation.
- d)Ingestion - Can cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

Chronic

OVEREXPOSURE to components of this mixture has been known to affect eyes, skin, kidney and liver damage.

PRIMARY ROUTES OF ENTRY:

- a)Skin
- b)Ingestion

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, and eye disorders may be aggravated by exposure to product.

EMERGENCY FIRST AID PROCEDURES:

- a)Skin - Wash with soap and running water.
- b)Eyes - Flush with large amounts of water, lifting upper and lower lids occasionally. Contact medical attention.
- c)Inhalation - If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d)Ingestion - Immediately drink 2 glasses of water, do not induce vomiting Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F) : 3344 SPECIFIC GRAVITY (WATER=1) : .834
VAPOR PRESSURE (mmHg) : 2 PERCENT VOLATILE BY VOLUME (%) . . . : >48
VAPOR DENSITY (AIR=1) : 4.9 EVAPORATION RATE (WATER=1) : >1
SOLUBILITY IN WATER: Slight POTENTIAL HYDROGEN (pH) : 9.0

APPEARANCE AND ODOR INFO: Yellowish opaque liquid (when shaken), solvent odor.

SECTION 5 - FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 1004F FTCC FLAMMABLE LIMITS: LEL= 1% UEL= N/E

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam.

SPECIAL FIRE FIGHTING PROCEDURES: Treat as Fuel Oil fire. Cool exposed containers with water spray. Firefighter should wear NIOSH/OSHA approved self contained breathing apparatus. NA1993 applies to components, product when used is basically non-flammable.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to heat associated with fire may rupture.

INCOMPATIBILITY (Material To Avoid):

Avoid contact with acids and strong oxidizers such as chlorine, permanganate, etc.

HAZARDOUS DECOMPOSITION PRODUCTS:

After water evaporates, burning may produce oxides of carbon, traces of sulfur and nitrogen oxides and various hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable absorbant. Wash the residue down the drain or pit with plenty of water. Small spills can be flushed down the drain with plenty of water.

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulations.

SECTION 7 - EXPOSURE CONTROL INFORMATION

VENTILATION: Use adequate volume to keep TLV/PEL below recommended levels and flammable limits in air below the level necessary to cause explosion or fire.

LOCAL EXHAUST: Below TLV(s) MECHANICAL (GENERAL): Comply with OSHA 1910.94

SPECIAL : N/A OTHER : N/A

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC-23C chemical/mechanical type filter system to remove the combination of particles, gas, and vapors. Use sir supplied respirator if necessary.

PROTECTIVE GLOVES: Not needed, unless prolonged use makes it necessary.

OTHER PROTECTIVE EQUIPMENT: Safety glasses or goggles with splash guards.

OTHER ENGINEERING CONTROLS: Eye wash and quick drench facilities.

WORK PRACTICES: Eye wash fountain and safety shower should be easily accessible. Towels, cloths, & rags used with product may be washed and reused. Provide adequate ventilation.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 8 - SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Do not store under freezing conditions or above 100 degrees F.
- b) Protect from physical damage and keep tightly closed.
- c) Do not store near acids or acidic materials and oxidizers.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

OTHER PRECAUTIONS:

- a) containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

SHIPPING INFO, NO UN/NA #'s, LABEL INFO NECESSARY OR SUGGESTED IN CFR's:

No label required, If Shipped mark containers:

Combustible Liquid, NOS, NA 1993, 3, Pk.Gp. III

KEEP OUT OF THE REACH OF CHILDREN!