

SECTION 1 - MANUFACTURER INFORMATION

MANUFACTURER/ DISTRIBUTOR: COMMODORE SALES, INC. 11002 TRADE ROAD RICHMOND, VA 23236
PREPARER/CONTACT: JOHN CROWE
EMERGENCY PHONE: (800)535-5053 (INFOTRACK)
INFORMATION PHONE: (804)794-1992

TRADE NAME / SYNONYMS: INTERIOR VINYL/ LEATHER RENEWER
CHEMICAL NAME / SYNONYMS: Silicon emulsion cleaner & polisher.
CHEMICAL FAMILY: Not Applicable.
FORMULA: Proprietary
PRODUCT CODE: 25-080

SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29B1910.1200 (i)-(13)
This product is a water soluble silicone based cleaner and polisher. None of the product's ingredients are found on any lists of banned chemical agents or materials generated by them.

THIS PRODUCT DOES NOT CONTAIN REGULATED PRODUCTS OR PRODUCTS THAT ARE KNOWN TO CAUSE CANCER: (NTP, IARC, OSHA):

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

Acute:

- a)Eyes - Can cause irritation, redness, tearing, blurred vision & swelling.
b)Skin - Prolonged or repeated contact can cause moderate irritation or redness.
c)Inhalation - Mild irritation.
d)Ingestion - Can cause gastro-intestinal irritation, nausea, vomiting, and diarrhea.

Chronic

PRIMARY ROUTES OF ENTRY:

- a)Ingestion

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to this product.

EMERGENCY FIRST AID PROCEDURES:

- a)Skin - Wash with soap and cool running water. Cease using product temporarily. Seek medical attention if irritation persists.
b)Eyes - Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. Get medical attention.
c)Inhalation - If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration.
d)Ingestion - Drink a large amount of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F) : 2124
VAPOR PRESSURE (mmHg) : N/D
VAPOR DENSITY (AIR=1) : N/D
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY (WATER=1) : 1.0
PERCENT VOLATILE BY VOLUME (%) : 10%
EVAPORATION RATE (Butyl Acetate=1): <1
POTENTIAL HYDROGEN (pH) : N/D

APPEARANCE AND ODOR INFORMATION: White semi viscous liquid, pleasant odor.

SECTION 5 - FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): >140 F. (COC)FLAMMABLE LIMITS: LEL= N/D UEL= N/D
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol Foam.
SPECIAL FIRE FIGHTING PROCEDURES: Treat as Fuel Oil fire. Cool exposed containers with water spray. Firefighter should wear NIOSH/OSHA approved self contained breathing apparatus. NA1993 applies to components, product when used is basically non-flammable.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to heat associated with fire may rupture.

INCOMPATIBILITY (Material To Avoid):

Avoid contact with acids and strong oxidizers such as chlorine, permanganate, etc.

HAZARDOUS DECOMPOSITION PRODUCTS:

After water evaporates, burning may produce oxides of carbon, traces of sulfur and nitrogen oxides and various hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable inert absorbent or, mop-up. Contain small spills and collect with inert absorbent material or dilute product with plenty of water and flush to the sewer. Comply with all governmental regulations on spill reporting, handling and disposal of waste.

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulations.

SECTION 7 - EXPOSURE CONTROL INFORMATION

VENTILATION: Use adequate volume to keep TLV/PEL below recommended levels and flammable limits in air below the level necessary to cause explosion or fire.

LOCAL EXHAUST: Below TLV(s) MECHANICAL (GENERAL): Comply with OSHA 1910.94

SPECIAL : N/A OTHER : N/A

RESPIRATORY PROTECTION: In confined areas or emergency situations, use NIOSH/MSHA TC-23C chemical/mechanical type filter system to remove the combination of particles, gas, and vapors. Use sir supplied respirator if necessary.

PROTECTIVE GLOVES: None required, unless prolonged use makes it necessary.

OTHER PROTECTIVE EQUIPMENT: Safety glasses or goggles with splash guards.

OTHER ENGINEERING CONTROLS: Eye wash and quick drench facilities.

WORK PRACTICES:

Eye wash fountain and safety shower should be easily accessible. Towels, cloths, & rags used with product may be washed and reused. Provide adequate ventilation to maintain exposure below TLV.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 8 - SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Do not store under freezing conditions or above 120 degrees F.
- b) Protect from physical damage and keep tightly closed.
- c) Do not store near acids or acidic materials and oxidizers.
- d) Keep away from sources that could ignite product container.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

OTHER PRECAUTIONS:

- a) containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

SHIPPING INFO, NO UN/NA #'s, LABEL INFO NECESSARY OR SUGGESTED IN CFR's:

No label required, If Shipped mark containers:

KEEP OUT OF THE REACH OF CHILDREN!