


MATERIAL SAFETY DATA SHEETS

SECTION 1 - MANUFACTURER INFORMATION

MANUF / DIST: COMMODORE SALES, INC.
11002 TRADE ROAD
RICHMOND, VA 23236
PREPARER/CONTACT: JOHN CROWE
RE ORDERING PHONE: 804-794-1992
MEDICAL/CHEMICAL EMERGENCY, 24 HOURS INFOTRAC 800-535-5053

TRADE NAME / SYNONYMS...: COMMODORE MOLECULAR PAINT SEALANT
CHEMICAL NAME / SYNONYMS: NOT APPLICABLE
CHEMICAL FAMILY.....: NOT APPLICABLE
FORMULA.....: Proprietary
PRODUCT CODE.....: LS-147

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:



SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS:	See CFR29§1910.1200 (i)-(13)			
CHEMICAL / COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH
Aliphatic Hydrocarbon	8002-05-9	>1	100PPM	100PPM
Trimethylbenzene	2551-13-7	>1	N/E	N/E
Proprietary Resin Compound (Proprietary)		>1	N/E	N/E
Trimethylbenzene	95-63-6	>1	N/E	N/E

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

MATERIAL SAFETY DATA SHEETS

SECTION 5 - FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 105°F T.C.C FLAMMABLE LIMITS: LEL-N/A UEL-N/A
EXTINGUISHING MEDIA: Regular foam, waterfog, carbon dioxide or dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES:

Clear fire area of unprotected personal. Do not enter confined fire area without full bunker gear, including a positive pressure mode breathing apparatus. Cool fire exposed containers with waterfog.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

* See additional Comments SECTION*

INCOMPATIBILITY (Material To Avoid):

Avoid contact with strong oxidizing agents such as chlorine, permanganate, etc.

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning may produce oxides of carbon and traces of hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Absorb on suitable absorbant and shovel into containers.

WASTE DISPOSAL METHODS:

Contaminated absorbant may be disposed of according to local, state and federal regulations for products containing petroleum distillates.

SECTION 7 - EXPOSURE CONTROL INFORMATION

VENTILATION:

LOCAL EXHAUST: Below TLV(s)

MECHANICAL (GENERAL): EXPLOSION PROOF

SPECIAL: N/A

OTHER: N/A

RESPIRATORY PROTECTION:

An appropriate NIOSH approved hydrocarbon canister or respirator for organic vapor should be worn if needed.